

# Calibre 1066M

## Base Calibre 1030

- Ø28.5mm
- Train: 18.000
- Automatic
- Anti-Magnetic
- Sweep second
- Shock Proof

1 : 1



7080



7081



7162



7163



7170



7176



7178




7185



7187



7181



7182

2 : 1



6973



7164



7173



7174



7177



7189

1030	<b>6973</b>	<i>Screw for: Fixing the movement</i>
1036	<b>7080</b>	<i>Center wheel with cannon pinion</i>
1036	<b>7081</b>	<i>Cannon pinion, height 2,65 mm</i>
1065 GMT	<b>7162</b>	<i>Balance cock</i>
1065 GMT	<b>7163</b>	<i>Stud holder</i>
1065 GMT	<b>7164</b>	<i>Screw for : Stud holder</i>
1065 <b>M</b>	<b>7170</b>	<i>Hour wheel, height 1,70 mm</i>
1065 <b>M</b>	<b>7173</b>	<i>Screw for : Balance</i>
1065 <b>M</b>	<b>7174</b>	<i>Screw for : Regulating the balance</i>
1065 <b>M</b>	<b>7176</b>	<i>Stud</i>
1065 <b>M</b>	<b>7177</b>	<i>Screw for : Stud</i>
1065 <b>M</b>	<b>7178</b>	<i>Roller complete</i>
1065 <b>M</b>	<b>7181</b>	<i>Anti-magnetic ring</i>
1065 <b>M</b>	<b>7182</b>	<i>Anti-magnetic back</i>
	<b>7185</b>	<i>Balance with Breguet hairspring, regulated</i>
	<b>7187</b>	<i>Bridge for self-winding mechanism</i>
	<b>7189</b>	<i>Set of screws for 1 watch movement</i>